


FIG.1






FIG.3

<	1
C	5
r	•

METER	RATE	_T1 RV_c_T1	_T2 RV_c_T2	••	RV_b_TN RV_c_TN
RV PARAMETER	CODING RATE CODING RATE 0<=x<=x2	RV_a_T1 RV_b_T1	RV_a_T2 RV_b_T2		RV_a_TN RV_b
COTIMATED	RECEPTION COUNT		2		Z




FIG.5

COD ING RA  O(=x(=x1)  COD ING RA  O(=x(=x1)  O(=x(=x1)	RV ESTIMATED TRANSMISSION COUNT	TE CODING RATE CODING RATE CODING RATE CODING RATE CODING RATE X1<	0 0 0 0	RV ESTIMATED TRANSMISSION COUNT 160AM	TE CODING RATE CODING RATE CODING RATE CODING $x1 < x < = x $ $x < x < = 1$ $0 < x < = y $ $0 < x < = x < x < = x < x < = x < x < = x < x <$	RV ESTIMATED IRANSMISSION COUNT QPSK 160AM	TE CODING RATE CODING RATE CODING RATE CODING RATE $x_1 < x_2 < x_3 < x_4 < x_5 < x$	0	RV ESTIMATED TRANSMISSION COUNT	16QAM	TE CODING RATE
		CODING RATE			X XI		CODING RATE  0<=x<=x1				CODING RATE

FIG.6

## 7/9

		CR=1/3			CR=1/2			. CR=4/5	
ř	3GPP [dB]	OPTIMAL RV DIF	DIFFERENCE [dB]	3GPP [dB]	OPTIMAL RV [dB]	OPTIMAL RV DIFFERENCE [dB]	3GPP [dB]	OPTIMAL RV [dB]	OPTIMAL RV DIFFERENCE [dB]
_	-11.0	-11.2	0.2	-8.3	-8.5	0.2	-3.5	-3.5	0.0
2	-14.3	-14.8	0.5	-12.9	-12.9	0.0	-8.6	-9.5	6.0
က	-16.6	-16.8	0.2	-14.2	-14.9	0.7	-11.8	-12.1	0.3
4	-18.2	-18.3	0.1	-16.1	-16.3	0.2	-13.4	-13.6	0.2




FIG.8




FIG.9